



Project: _____
Model: _____ Series #: _____
Dealer: _____ Quantity#: _____
Delivery address: _____ Date: _____

Bottom Mounted Series Reach in Solid door

Model#UM54R



Features

- Precision ventilated refrigeration system keeps food at safe temperature
- Electronic control system make it easy to adjust temperature set point and defrost frequency
- Self closing door with 90 degree stay open feature,locks and keys included
- Preinstalled heavy duty casters with brakes
- Removeable installation board makes it easy to access condenser coil for cleaning and service.
- Stainless steel exterior and interior, ensure longer life
- Full lighting vertical LED light,goes on when door open, goes off when door closed
- Anti-corrosion coated copper coil evaporator, and 100% copper coil condenser ensure 10 years life of During products
- 8 epoxy coated steel wire shelves, 155 lbs loading capacity each.
- R290 hydro carbon refrigerant that has zero(0) ozone depletion potential(ODP) & three(3) global warming potential(GWP)

WARRANTY:

- 2 Years Parts and Labor
- 6 Years compressor (Additional 4 years parts only)
- During is responsible for components failure.But is not responsible for improper operation failure and artificial damage



Parts & Labor



Compressor



Conforms to UL&NSF-7 Standards





Bottom Mounted Series Reach in Solid door

Model#UM54R

TECHNICAL DATA

Model #	UM54R
Temperature range	33~41°F
Refrigerant	R290
Max Ambient Temperature	100°F
Defrosting	automatic every 4 hours
Horsepower	1/3
Exterior Dimension	54 1/10"Wx30.7"Dx81 9/10"H
Interior Dimension	50 2/5"Wx24 1/5"Dx59 13/20"H
Gross Weight	480lbs
Net Weight	436lbs
Packing Dimension	55 9/10"Wx33"Dx84 3/5"H
Voltage/Phase/Hz	115V/1/60HZ
Amps	5.4
Plug Type	NEMA 5-15P
Electrical Cord Length	80"

PLAN VIEW

